




## Lnb-kpxx v1



LNB-KPxx v1 is a PLL LNB with single local oscillator and single 75Ohm F-type output. LO instability  $\pm 25$  kHz, Gain 50dB, Noise figure 1.6 dB, Output power P1dB +5 dBm.

The Low Noise Block Down Converter LNB-KPxx v1 designed for gain and transform the RF signals from K-band to the L-band intermediate frequencies. This block has a waterproof case and could be mounted in close proximity to an antenna. LNB's Parameters correspond to the conditions of MVDS/MITRIS TV broadcasting systems according to standard DVB-S/S2 and could be operates up to 25 carriers. LNB-KPxx v1 has input flange PBR220 and could be used with regular RRL or receive antennas.

**This LNB could be supplied with next value of Local Oscillator:**

- **LO** 17.25 GHz **IN:** 18.2 - 19.20 GHz **OUT:** 950 - 1950 MHz
- **LO** 18.25 GHz **IN:** 19.2 - 20.20 GHz **OUT:** 950 - 1950 MHz
- **LO** 19.25 GHz **IN:** 20.2 - 21.20 GHz **OUT:** 950 - 1950 MHz
- **LO** 20.25 GHz **IN:** 21.2 - 21.85 GHz **OUT:** 950 - 1600 MHz

### KEY FEATURES:

- Flange PBR220 input
- Output power is P1dB +5 dBm
- Input frequencies any 1000 MHz in K-band
- Output frequencies 950 - 1950 MHz
- Min. gain 50 dB
- Oscillator type PLL
- Operates up to 25 carriers
- Designed for operation in MVDS/MITRIS TV broadcasting systems

Input parameters:	
<b>Input Frequency range</b>	18.2- 19.2 GHz (or any 1000 MHz in K-band by order)
<b>Input level, max</b>	-50 dBm
<b>Input VSWR, max</b>	2.2
<b>Input interface</b>	Waveguide WR42, Flange PBR220
Local Oscillator:	
<b>LO frequency</b>	17.25GHz (or by order: 18.25, 19.25, 20.25 GHz )
<b>LO Phase noise:</b>	
<b>@1 kHz</b>	-70 dBc/Hz
<b>@10 kHz</b>	-80 dBc/Hz
<b>LO instability</b>	$\pm 25$ kHz (or by order: $\pm 50$ kHz, $\pm 70$ kHz)
Output parameters:	

<b>Output frequency range</b>	950 - 1950 (or by order)
<b>Output Power @P1dB</b>	+5 dBm
<b>Gain, min</b>	55 dB
<b>Output interface</b>	F-type female (or N-type female by order)
<b>Output impedance</b>	75 Ohm (50 Ohm by order)
<b>Output VSWR, max</b>	2.2
<b>Frequency Response:</b>	
<b>Flatness over Full Band</b>	±2 dB
<b>Flatness over 27MHz Band</b>	±0.75 dB
<b>Spurious:</b>	
<b>Noise Figure (@+25°C)</b>	1.6 dB max
<b>LO leakage, max</b>	-50 dBm
<b>Image rejection, min</b>	40 dBc
<b>Power Supply:</b>	
<b>Input voltage</b>	12 VDC - 24 VDC, nominal 18 VDC
<b>Power consumption, max</b>	3.6 W
<b>Environmental:</b>	
<b>Operating temperature</b>	-30°C to +60°C (-22°F to +140°F)
<b>Storage temperature</b>	-40°C to +80°C (-40°F to +176°F)
<b>Operating humidity</b>	0% - 95%
<b>Mechanical</b>	
<b>Dimensions (W x H x D)</b>	60x42x116.8 mm
<b>Weight</b>	0.4 kg

Taking into consideration that we (ROKS PrJSC) are developer and system integrator, also do not stop on our technical growth and improvement, know that view of all our devices and equipment including their technical parameters may be different from pictures presented on website and parameters listed on each device webpage.

**Note!** All details customer has to confirm in advance during ordering and before payment. Those parameters that were not specified and / or were not agreed while ordering will be implemented as basic at the discretion of the manufacturer. Each our customer has 1.5 year warranty and 7 year aftersales support for whole range of our products.