Modulator dvb-c / s / t

DVB-S / DVB-C / DVB-T Modulator unit is professional equipment for using by operators of television networks and performs modulation up to QAM256. Modulator has from 1 to 6 independent channels formed in a single housing 19” height 1U or 2U.

DVB-S / DVB-C / DVB-T Modulator unit is professional equipment for using by operators of television networks and performs modulation up to QAM256. Modulator has from 1 to 6 independent channels formed in a single housing 19” height 1U or 2U. This device performs modulation digital stream RF carrier frequency in a wide range (70 - 865 MHz or 950 - 2150 MHz) according to the standards DVB-S, DVB-C, DVB-T

KEY FEATURES:

- Frequency range: 70 - 865 MHz (DVB-C and DVB-T) or 950 - 2150 MHz (DVB-S)
- Support DVB-S, DVB-C and DVB-T standards
- Constelation QPSK, QAM16, QAM32, QAM64, QAM128, QAM256
- Hight modulation error rate (MER)
- Input bitrate up to 45 Msps
- Output level 80-107 dBµV
- Optionally 10 MHz reference and DC injection

Taking into consideration that we (ROKS PrJSC) are developer and system integrator, also do not stop on our technical growth and improvement, know that view of all our devices and equipment including their technical parameters may be different from pictures presented on website and parameters listed on each device webpage.
***Note!** All details customer has to confirm in advance during ordering and before payment. Those parameters that were not specified and / or were not agreed while ordering will be implemented as basic at the discretion of the manufacturer. Each our customer has 1.5 year warranty and 7 year aftersales support for whole range of our products.*