



Ird crt1082ipe



Integrated Receiver Descrambler (IRD) is a compact size 8-channel head-end with 8 CI slots for channels descrambling.

Integrated Receiver Descrambler (IRD) is a compact size 8-channel head-end with 8 CI slots for channels descrambling.

DVB-S2 receiver	
Number of channels	8
Receiving frequency range	950-2150 MHz
Input signal level	-65-25 dBm
Nominal RF input impedance	75 Ohm
Connector type	I EC, F-type
Modulation	QPSK, 8PSK, 16APSK
Symbol Rate	1 -45Msps(QPSK,8PSK), 1 -36Msps(16APSK)
FEC	1/2, 3/5, 2/3, 3/4, 4/5, 5/6, 6/7, 7/8, 8/9, 9/10
Common Interface	
Number of channels	8
Specification	EN50221, ETSI TS 101699
DVB-ASI Output	
Number of channels	8
Specification	EN 50083-9
Output impedance	75 Ohm
Connector type	IEC 169-8, BNC-type
Operation modes	Packet, 188 byte
Maximum output bit rate	213 Mbps
DVB-over-IP	
Specification	ETSI TS 102034
Streaming protocols	RTP, UDP
Number of multicast streams	64 (SPTS)
Number of unicast connections	8 (MPTS)
Network interface	1Gbit Ethernet

Taking into consideration that we (ROKS PrJSC) are developer and system integrator, also do not stop on our technical growth and improvement, know that view of all our devices and equipment including their technical parameters may be different from pictures presented on website and parameters listed on each device webpage.

Note! *All details customer has to confirm in advance during ordering and before payment. Those parameters that were not specified and / or were not agreed while ordering will be implemented as basic at the discretion of the manufacturer. Each our customer has 1.5 year warranty and 7 year aftersales support for whole range of our products.*