



Psu 12-24v

www.roks-ty.com



Power supply unit 12 - 24V, 36W has stabilized voltage $\pm 1V$ and output short circuit protection, fuse protected. Designed for powering of receiving and transmitting units through the DC injectors.

KEY FEATURES:

- Input voltage ~100 - 240 V
- Output voltage range 12 V - 24 V
- Output power 36W

Outputs	
Output voltage	12 V - 24 V
Output power	36W
Output current	3.0A @ 12V; 1.5A: 24V
Noise	$\leq 0.5\%$
Swinching freuquency	65 - 130 kHz
Temperature instability	$\leq 1\%$
Input	
Input voltage	~100 - 240 V
Input frequency	40 - 400 Hz
Efficiency	$\geq 85\%$ @ 12V; $\geq 88\%$ @ 24V;
Protection	
Max power	43 W
Output short circuit protection	automatical
Environmental	
Operating Temperature	-25°C to +70°C
Storage Temperature	-40°C to +85°C
Operating Humidity	20% - 90%
Mechanical	
Dimensions (W x H x D)	97 x 45 x 17 mm
Weight	0.680 kg

Taking into consideration that we (ROKS PrJSC) are developer and system integrator, also do not stop on our technical growth and improvement, know that view of all our devices and equipment including their technical parameters may be different from pictures presented on website and parameters listed on each device webpage.

Note! All details customer has to confirm in advance during ordering and before payment. Those parameters that were not specified and / or

were not agreed while ordering will be implemented as basic at the discretion of the manufacturer. Each our customer has 1.5 year warranty and 7 year aftersales support for whole range of our products.